

Viento

Compact Wall Heater



Surface

Recessed



The Viento wall heater has clean lines and rounded corners which match perfectly with any decor. Its compact size makes this heater perfect for areas with limited space. It can be installed recessed or on the wall surface with 4 different mounting positions, adapting to any installation requirement.



Features

Color

- Standard:



- Optional (10\$ upcharge and 5 days production lead time):



Note: Due to the printing, the colors may vary from the actual colors.

Finish

- Standard: epoxy/polyester powder paint.

Voltage

- 120V, 240/208V, 1-phase.

Construction

- 20-gauge steel cabinet.
- 22-gauge steel front cover.
- High-limit temperature control with automatic reset.

Fan

- Quiet fan operating.
- 500W to 1000W; 40 cfm fan and 1250W to 2000W; 80 cfm fan.
- Factory-lubricated motor.

Heating element

- Durable tubular heating element with fins.

Control

- Built-in thermostat available with a control knob.
- Note: If an electronic thermostat is used, it must be compatible with forced-air heaters.*

Installation

- Wall installation only.
- The air outlet should be installed at least 4 in. (102 mm) from flooring withstands temperature and 10 in. (254 mm) from linoleum flooring.
- Quick installation with recess box mounting holes.
- Large wiring compartment.
- May be recessed in 2 in. X 3 in. stud partitions.
- Surface mounting box available.
- Tight fit with V-shaped recess box.

Warranty

- 5-year warranty against defects.

Application

- Entrance way, kitchen, bathroom, family room, basement.

Viento - Compact Wall Heater

Models			
Watts	Volts	Product #	Price
500	120	OVS0502	279.00
1000	120	OVS1002	297.00
1500	120	OVS1502	323.00
500/375	240/208	OVS0500	274.00
1000/750	240/208	OVS1000	289.00
1500/1125	240/208	OVS1500	319.00
2000/1500	240/208	OVS2000	345.00

Options		
Product #	Price	Description
KIT-OVS-BS	67.00	Surface mounting box
KIT-OVS-TB6	59.00	Single-pole bi-metal thermostat kit with a control knob
KIT-OVS-TB26 ¹	72.00	Double-pole bi-metal thermostat kit with a control knob

¹ «Off» position.
Add «BL» for white, «AM» for almond.

Four mounting positions available. Pictures showing front panel. Directional vane air flow.

